

**SURFACE MOUNTED, 400 M INDUSTRIAL ROLLS  
STEEL WHITE EPOXY**

**Code: PR0787**

**General description**

- Toilet paper dispenser for industrial rolls of 400 m, surface mounted, steel white epoxy coated.
- Manual dispensing.
- Robust and vandal-proof.
- Suitable for very high traffic facilities.
- Model suitable for public use.
- It generally goes along with a toilet brush and waste receptacle, steel white epoxy coated, complemented by a warm air hand dryer.

**Components & Materials**

- Steel white epoxy coated one-piece body, 0,8 mm thick, round Ø 300 mm, fully sealed and with a catch system to prevent the opening of the door. The supports of the screws in the back of the appliance, are acting as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It is mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It includes a lock system with standard mediclinics® key, that allows opening the lid for replenishment.
- Stainless steel AISI 304 white epoxy coated axis, 0,8 mm thick, for standard 45 mm paper roll tube, with inertial anti-spin retainer. The axis allows the use of a standard paper roll in case of need.
- Steel white epoxy coated one-piece seamless lid, 0,8 mm thick, fully sealed. Fixed to the body by means of rivets that allows swinging down of the lid for the replenishment.
- Frontal window indicates refill time.

**Technical Specifications**

Dimensions	Ø 300 x 123 mm	1 layer paper roll capacity	400 m
Maximum dimensions	307 x 300 x 123 mm	2 layers paper roll capacity	300 m
Weight (empty)	1,75 Kg	Paper roll diameter	274 mm (maximum)
Recommended installation height	65-75 cm to bottom	Paper roll width	115 mm (maximum)
Installation height for disabled people	70 cm from the floor	Paper roll tube diameter	45 mm (minimum)

**Operation**

Pull visible toilet paper, at your own convenience.




**Certificates & Qualifications**

ISO 9001:2000.

**Specification**

Surface mounted toilet paper dispenser for industrial rolls of 400 m should be made of steel white epoxy coated one-piece body, 0,8 mm thick, round Ø 300 mm, fully sealed and with a catch system to prevent the opening of the door. The supports of the screws in the back of the appliance should be act as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It should be suitable to be mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It should include a lock system with standard mediclinics® key, that allows opening the lid for replenishment. The axis should be made of stainless steel AISI 304, 0,8 mm thick, for standard 45 mm paper roll tube, with inertial anti-spin retainer. The axis should allow the use of a standard paper roll in case of need. The lid should be made of steel white epoxy coated one-piece seamless, 0,8 mm thick, fully sealed and fixed to the body by means of rivets that allows swinging down of the lid for the replenishment. The dispenser should have a frontal window which indicates refill time. Overall dimensions shall be Ø 300 x 123 mm.

Toilet paper dispenser for industrial rolls of 400 m shall be model PR0787, steel white epoxy coated, manufactured by Mediclinics S.A., C/ Industria 54, E-08025 Barcelona, Spain.



Dim ± 4%

**Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without warning or notice.**

**Revision 4-2004**

© mediclinics S.A.

