

TOILET PAPER DISPENSER MEDICLINICS ®

SURFACE MOUNTED, TWO STANDARD ROLLS STEEL WHITE EPOXY

General description

- Toilet paper dispenser for two standard rolls, surface mounted, steel white epoxy coated.
- Manual dispensing.
- Suitable for high traffic facilities.
- Model suitable for public use.
- It generally goes along with a toilet brush holder and toilet paper waste receptacle, steel white epoxy

Components & Materials

- Steel white epoxy coated one-piece body, 0,8 mm thick, fully sealed. The
 supports of the screws in the back of the appliance, are acting as an antimoisture support, as well as slots to avoid the screws damaging the toilet
 paper. It is mounted on the wall by means of 3 wood screws with their
 corresponding 5 mm wall plugs. It includes a lock system with standard
 mediclinics® key, that allows opening the lid for replenishment.
- Steel white epoxy coated one-piece seamless lid, 0,8 mm thick, fully sealed. Fixed to the body by means of 2 rivets that allows swinging of the lid for the replenishment through the top opening. The extra tissue rolls descend when the previous one has been finished, by a simple hand manipulation through the side window. There is no need to open the lid for the removal of consumed rolls.
- Frontal sight-hole and slots on each side of body indicate refill time.

Technical Specifications 290 x 116 x 130 Toilet paper **Dimensions** 2 u roll capacity mm Toilet paper Weight (empty) 0,9 Kg Ø 105-125mm roll diameter Recommended 65-75 cm to Toilet paper 110 mm installation height bottom roll width (maximum) Installation height 70 cm from the for disabled floor people

Operation

Pull visible toilet paper, at your own convenience.

Certificates & Qualifications

ISO 9001:2000.

116 mm (4-5/8") 290 mm (11-3/8" 130 mm (5-1/8") 290 mm (11-3/8") 130 mm (5-1/8") 60 mm (2-3/8") 185 mm (7-1/4") Dim ± 4%

Code: PR0784

Specification

Surface mounted toilet paper dispenser for two standard rolls should be made of steel white epoxy coated. The body should be made of steel white epoxy coated one-piece, 0,8 mm thick, fully sealed. The supports of the screws in the back of the appliance should be act as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It should be suitable to be mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It should include a lock system with standard mediclinics® key, that allows opening the lid for replenishment. The lid should be made of steel white epoxy coated one-piece seamless, 0,8 mm thick, fully sealed. The lid should be fixed to the body by means of 2 rivets that allows swinging of the lid for the replenishment through the top opening. The extra tissue rolls should descend when the previous one has been finished, by a simple hand manipulation through the side window. To open the lid should be no needed for the removal of consumed rolls. The appliance should contain front sight-hole and slots on each side of body to indicate refill time. Overall dimensions shall be 290 x 116 x 130 mm.

Toilet paper dispenser for two standard rolls shall be model PR0784, steel white epoxy coated, manufactured by Mediclinics S.A., C/ Industria 54, E-08025 Barcelona, Spain.

Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without warning or notice.

ISO 9001

Revision 4-2004 © mediclinics S.A.