BOBRICK

Technical Data

SURFACE-MOUNTED TOWEL BAR

B-7674 B-76747

Specify Model Required: ☐ Model B-7674 Bright polished stainless steel
☐ Model B-76747 Satin-finish stainless steel





STANDARD STOCK SIZES

Model No.	Bar Length L	Overall Length X	Centerline-to-Centerline Y
B-7674 x 18	18" (455mm)	19-5/8" (500mm)	17-5/8" (450mm)
B-76747 x 18	18" (455mm)	19-5/8" (500mm)	17-5/8" (450mm)
B-7674 x 24	24" (610mm)	25-5/8" (650mm)	23-5/8" (600mm)
B-76747 x 24	24" (610mm)	25-5/8" (650mm)	23-5/8" (600mm)
B-7674 x 30	30" (760mm)	31-5/8" (805mm)	29-5/8" (750mm)
B-76747 x 30	30" (760mm)	31-5/8" (805mm)	29-5/8" (750mm)

MATERIALS:

Flanges & Support Arms (2) — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel. Each flange has a concealed, 18-gauge (1.2mm) stainless steel mounting bracket. All-welded construction. Secured to wall plates with stainless steel setscrews.

Concealed Wall Plates (2) — 18-8 S, type-304, 19-gauge (1.0mm) stainless steel.

Towel Bar — 18-8 S, type-304, heavy-gauge stainless steel. Seamless, 3/4" (19mm) diameter tubing.

INSTALLATION:

To remove concealed wall plates from back of flanges and mounting brackets, loosen setscrews. Mount each wall plate so prongs are at top; secure with sheet-metal screws, furnished by manufacturer, at points indicated by an *S*. Engage mounting brackets onto prongs of wall plates, then secure unit into position by tightening setscrews at bottom of flanges.

Note: Centerline-to-centerline of concealed wall plates must be within 1/16" (1.6mm) of dimension (Y) shown in table above.

For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws furnished. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.

SPECIFICATION:

Surface-mounted towel bar shall be type-304 stainless steel with _____ (insert one: bright polished or satin) finish. Flanges and support arms shall be 22 gauge (0.8mm) and equipped with concealed, 18-gauge (1.2mm) mounting brackets that are secured to concealed, 19-gauge (1.0mm) wall plates with stainless steel setscrews. Towel bar shall be seamless, 3/4" (19mm) diameter tubing. Manufacturer's service and parts manual shall be provided to the building owner/manager upon completion of project.

Surface-Mounted Towel Bar shall be Model _____ (insert model number) of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment of Canada Ltd., Scarborough, Ontario; Bobrick Washroom Equipment Pty. Ltd., Australia; Bobrick Washroom Equipment Limited, United Kingdom.

The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet. Revised 8/99 Printed in U.S.A.
The manufacturer reserves the right to, and does from time to time, make changes and improvements in designs and dimensions. © 1999 by Bobrick Washroom Equipment, Inc.